

# U ∩ İ Î Wireless Control Module



## **Product Summary**

#### **Features**

JenNet-IP Compatible 0-10V Dimming Control Integrated Low Power Sleep Mode 128-bit AES Security IEEE802.15.4 2.4 GHz Compliant Utility Grade Power Metering Tri-Color Status LED Color Coded Wiring Fits in Stadard 3/4" Knockout Ready for Retrofits

## Wiring

Black: Line/ Hot Input

White: Neutral

Red: Switched Line/ Hot Output

Grev: 0-10V -Violet: 0-10V +

UL 244A UL 1310







#### unifi<sub>™</sub> enabled wireless control module

The unifi<sub>™</sub> relay lighting control module enables wireless control of on/off and 0-10V dim functions for incandescent, LED, and Halogen lamps. On board power metering circuitry records and conveys energy usage data to the unifi cloud. The relay enables smart controls and use metrics without expensive signal wires, making it the ideal solution for retrofits and new construction.

### **Technical Specifications**

Cloud Compatibility

Input Voltage	100~277VAC 50-60Hz
Load Current Rating	N/O Contacts 10A@100~277VAC
Dimming Control Signa	0-10V IEC 60929 Sinking Compatible
Radio Frequency	2.4GHz
Operating Environment	-20°c to +70°c IP54
Compliance	UL 244A, UL 1310, FCC Part 15
FCC ID	TYOJN5168M3
Mounting	Screw Tabs 3/4" NPT Knockout
Dimensions	2.5" X 2.125" X 1.5" nominal

Wireless Range ~100' upgradable with external antennas

unifi ™